



INMESOL AI-033 (OPEN) / II-033 (CLOSED)





GENERAL SET DATA

ENGINE REF:	F32AM1A
ALTERNATOR REF:	ECP 28-VL/4
STANDARD CONTROL PANEL:	DSE 6020
OPTIONAL CONTROL PANEL:	-

OUTPUT

FREQUENCY:	50 hz
VOLTAGE:	400/230
PRIME POWER:	30 kVA
STANDBY POWER:	33 kVA

DIMENSIONS

OPEN MODEL (AI-033)

LENGTH:	1700 mm
WIDTH:	730 mm
HEIGHT:	1634 mm
DRY WEIGHT:	680 Kg
FUEL TANK CAPACITY:	105 L

CLOSED MODEL (II-033)

LENGTH:	2000 mm
WIDTH:	950 mm
HEIGHT:	1353 mm
DRY WEIGHT:	980 Kg
FUEL TANK CAPACITY:	85 L
ACOUSTIC PRESSURE AT 1M:	-
ACOUSTIC PRESSURE AT 7M:	62 dB





info@npr-uk.com www.newburnpowerrental.com

INMESOL AI-033 (OPEN) II-033 (CLOSED)

TECHNICAL DATA

GENERAL ENGINE DATA

MANUFACTURER:	FPT
MODEL REF:	F32AM1A
SPEED:	1500 RPM
POWER PRP:	28.5 kWm
POWER LTP:	31.5 kWm
NUMBER OF CYLINDERS:	4
DISPLACEMENT:	3.2 L
BORE:	108 mm
STROKE:	1130 mm
COMPRESSION RATIO:	17
COOLING SYSTEM:	LIQUID
AIR INLET SYSTEM:	NATURAL
OIL CAPACITY:	10 L
EXHAUST GAS TEMP:	400 °C
EXHAUST GAS FLOW:	338 m³/h

ALTERNATOR DATA

ALTERNATOR REF: MECC-ALTE ECP 28-VL/4

INSULATION CLASS: H

INDICATION OF PROTECTION: IP23

FUEL

CONSUMPTION AT 100%:	9.6 L/hr
CONSUMPTION AT 75%:	6.5 L/hr
CONSUMPTION AT 50%:	4.3 L/hr

TERMS & CONDITIONS

THE MACHINE HOLDS THE "CE" MARKING, AND THE CORRESPONDING DECLARATION OF CONFORMITY IS ISSUED WITH EACH OF THEM, IN WHICH IT SPECIFIES THAT THE MACHINE COMPLIES WITH R.D 842/2002 LOW VOLTAGE REGULATIONS AND WITH THE EUROPEAN DIRECTIVES: 2006/42 ON SAFETY IN MACHINERY, 2006/95/CE ON ELECTRICAL SAFETY, 2004/108/CE ON ELECTROMAGNETIC COMPATIBILITY, 2005/88/CE ON NOISE EMISSIONS BY EQUIPMENT FOR OUTDOOR USE (FOR SOUNDPROOF GENERATOR SETS).