

INMESOL AI-220 (OPEN) / II-220 (CLOSED)



GENERAL SET DATA

ENGINE REF:	N67TE2A
ALTERNATOR REF:	ECO 38-2SN
STANDARD CONTROL PANEL:	DSE 3110
OPTIONAL CONTROL PANEL:	DSE 334

OUTPUT

FREQUENCY:	50 hz
VOLTAGE:	400/230
PRIME POWER:	200 kVA
STANDBY POWER:	220 kVA

DIMENSIONS

OPEN MODEL (AI-220)

LENGTH:	2360 mm
WIDTH:	1035 mm
HEIGHT:	1980 mm
DRY WEIGHT:	1540 Kg
FUEL TANK CAPACITY:	320 L

CLOSED MODEL (II-220)

LENGTH:	3600 mm
WIDTH:	1350 mm
HEIGHT:	2040 mm
DRY WEIGHT:	2580 Kg
FUEL TANK CAPACITY:	360 L
ACOUSTIC PRESSURE AT 1M:	-
ACOUSTIC PRESSURE AT 7M:	71 dB

INMESOL AI-220 (OPEN) II-220 (CLOSED)

TECHNICAL DATA

GENERAL ENGINE DATA

MANUFACTURER:	FPT
MODEL REF:	N67TE2A
SPEED:	1500 RPM
POWER PRP:	175 kWm
POWER LTP:	193 kWm
NUMBER OF CYLINDERS:	6
DISPLACEMENT:	6.7 L
BORE:	104 mm
STROKE:	132 mm
COMPRESSION RATIO:	17.5
COOLING SYSTEM:	LIQUID
AIR INLET SYSTEM:	TURBO
OIL CAPACITY:	17 L
EXHAUST GAS TEMP:	550 °C
EXHAUST GAS FLOW:	2102 m ³ /h

ALTERNATOR DATA

ALTERNATOR REF:	MECC-ALTE ECO 38-2SN
INSULATION CLASS:	H
INDICATION OF PROTECTION:	IP21

FUEL

CONSUMPTION AT 100%:	44 L/hr
CONSUMPTION AT 75%:	35.7 L/hr
CONSUMPTION AT 50%:	25.6 L/hr

TERMS & CONDITIONS

Inmesol power GENSET sets comply with European legislation and were given the CE marking. It also complies with International Legislation and Regulations, "Technical Regulation on Safety of Machinery & Equipment" No. 753, repealing GOST R standards for exports to Russia. Resolution 90708 dated August 30th 2013 "Reglamento Tecnico de Instalaciones Electricas RETIE" issues by the Ministry of Mining and Energy Section 20.21 Engines and power generators, for exports to Colombia.