


## SDMO J165K



### GENERAL SET DATA

ENGINE REF:	6068HF120-153
ALTERNATOR REF:	KH01340T
STANDARD CONTROL PANEL:	APM303
OPTIONAL CONTROL PANEL:	APM403
	M80/TELYS

### OUTPUT

FREQUENCY:	50 Hz
VOLTAGE:	400/230
PRIME POWER:	150 kVA
STANDBY POWER:	165 kVA

### DIMENSIONS

#### OPEN MODEL

LENGTH:	2370 mm
WIDTH:	1114 mm
HEIGHT:	1470 mm
DRY WEIGHT:	1578 Kg
FUEL TANK CAPACITY:	340 L

#### CLOSED MODEL

LENGTH:	3508 mm
WIDTH:	1200 mm
HEIGHT:	1830 mm
DRY WEIGHT:	2198 Kg
FUEL TANK CAPACITY:	340 L
ACOUSTIC PRESSURE AT 1M:	75 dB
ACOUSTIC PRESSURE AT 7M:	64 dB

# SDMO J165K

## TECHNICAL DATA

### GENERAL ENGINE DATA

MANUFACTURER:	JOHN DEERE
MODEL REF:	6068HF120-153
SPEED:	1500 RPM
POWER PRP:	120 kW
POWER LTP:	132 kW
NUMBER OF CYLINDERS:	6
DISPLACEMENT:	6.72 L
BORE:	106 mm
STROKE:	127 mm
COMPRESSION RATIO:	17
COOLING SYSTEM:	GLYCOL-ETHYLENE
AIR INLET SYSTEM:	TURBO
OIL CAPACITY:	21.5 L
EXHAUST GAS TEMP:	555 °C
EXHAUST GAS FLOW:	385 L/s

### ALTERNATOR DATA

ALTERNATOR REF:	KH01340T
INSULATION CLASS:	H
INDICATION OF PROTECTION:	IP23

### FUEL

CONSUMPTION AT 100%:	33.5 L/h
CONSUMPTION AT 75%:	25 L/h
CONSUMPTION AT 50%:	17 L/h

### TERMS & CONDITIONS

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

According to the standard, the nominal power assigned by the genset is given for 25°C Air Intlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.