

SDMO K17M



GENERAL SET DATA

ENGINE REF:	KDW1903M
ALTERNATOR REF:	KH00630T
STANDARD CONTROL PANEL:	APM303
OPTIONAL CONTROL PANEL:	TELYS/M80

OUTPUT

FREQUENCY:	50 Hz
VOLTAGE:	230
PRIME POWER:	14.1 kVA
STANDBY POWER:	15.5 kVA

DIMENSIONS

OPEN MODEL

LENGTH:	1410 mm
WIDTH:	720 mm
HEIGHT:	1080 mm
DRY WEIGHT:	530 Kg
FUEL TANK CAPACITY:	50 L

CLOSED MODEL

LENGTH:	1750 mm
WIDTH:	775 mm
HEIGHT:	1230 mm
DRY WEIGHT:	700 Kg
FUEL TANK CAPACITY:	50 L
ACOUSTIC PRESSURE AT 1M:	71 dB
ACOUSTIC PRESSURE AT 7M:	58 dB

SDMO K17M

TECHNICAL DATA

GENERAL ENGINE DATA

MANUFACTURER:	KOHLER
MODEL REF:	KDW1903M
SPEED:	1500 RPM
POWER PRP:	14.1 kW
POWER LTP:	15.5 kW
NUMBER OF CYLINDERS:	3
DISPLACEMENT:	1.86 L
BORE:	88 mm
STROKE:	102 mm
COMPRESSION RATIO:	18.5
COOLING SYSTEM:	GLYCOL-ETHYLENE
AIR INLET SYSTEM:	ATHMO
OIL CAPACITY:	8.7 L
EXHAUST GAS TEMP:	520 °C
EXHAUST GAS FLOW:	59 L/s

ALTERNATOR DATA

ALTERNATOR REF:	KH00630T
INSULATION CLASS:	H
INDICATION OF PROTECTION:	IP23

FUEL

CONSUMPTION AT 100%:	4.5 L/hr
CONSUMPTION AT 75%:	3.3 L/hr
CONSUMPTION AT 50%:	2.3 L/hr

TERMS & CONDITIONS

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

According to the standard, the nominal power assigned by the genset is given for 25°C Air Intlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.