

SDMO T9KM



GENERAL SET DATA

| | |
|-------------------------|--------------|
| ENGINE REF: | S3L2-SD |
| ALTERNATOR REF: | KH00470T |
| STANDARD CONTROL PANEL: | APM303 |
| OPTIONAL CONTROL PANEL: | TELYS M80 |

OUTPUT

| | |
|----------------|---------|
| FREQUENCY: | 50 Hz |
| VOLTAGE: | 230 |
| PRIME POWER: | 7.8 kVA |
| STANDBY POWER: | 8.6 kVA |

DIMENSIONS

OPEN MODEL

| | |
|---------------------|---------|
| LENGTH: | 1405 mm |
| WIDTH: | 715 mm |
| HEIGHT: | 1053 mm |
| DRY WEIGHT: | 396 Kg |
| FUEL TANK CAPACITY: | 50 L |

CLOSED MODEL

| | |
|--------------------------|---------|
| LENGTH: | 1750 mm |
| WIDTH: | 775 mm |
| HEIGHT: | 1230 mm |
| DRY WEIGHT: | 544 Kg |
| FUEL TANK CAPACITY: | 50 L |
| ACOUSTIC PRESSURE AT 1M: | 71 dB |
| ACOUSTIC PRESSURE AT 7M: | 58 dB |

SDMO T9KM

TECHNICAL DATA

GENERAL ENGINE DATA

| | |
|----------------------|-----------------|
| MANUFACTURER: | MITSUBISHI |
| MODEL REF: | S3L2-SD |
| SPEED: | 1500 RPM |
| POWER PRP: | 7.8 kW |
| POWER LTP: | 8.6 kW |
| NUMBER OF CYLINDERS: | 3 |
| DISPLACEMENT: | 1.32 L |
| BORE: | 78 mm |
| STROKE: | 92 mm |
| COMPRESSION RATIO: | 22 |
| COOLING SYSTEM: | GLYCOL-ETHYLENE |
| AIR INLET SYSTEM: | ATHMO |
| OIL CAPACITY: | 4.2 L |
| EXHAUST GAS TEMP: | 400 °C |
| EXHAUST GAS FLOW: | 36.5 L/s |

ALTERNATOR DATA

| | |
|---------------------------|----------|
| ALTERNATOR REF: | KH00470T |
| INSULATION CLASS: | H |
| INDICATION OF PROTECTION: | IP23 |

FUEL

| | |
|----------------------|-------|
| CONSUMPTION AT 100%: | 0 L/h |
| CONSUMPTION AT 75%: | 0 L/h |
| CONSUMPTION AT 50%: | 0 L/h |

TERMS & CONDITIONS

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

According to the standard, the nominal power assigned by the genset is given for 25°C Air Intlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.